

Docket No. AT9-99-697

## INTEROPERABLE/HETEROGENEOUS ENVIRONMENT KEYBOARD

### BACKGROUND OF THE INVENTION

5

#### 1. Technical Field:

The present invention relates generally to data processing systems and, more specifically, to methods of efficiently utilizing space allocated to storing data processing systems and associated peripheral devices.

10

#### 2. Description of Related Art:

Computers perform many functions in today's society, often performing tasks and monitoring processes with minimal or no human intervention. Many businesses and service providers may have rooms or laboratories filled with numerous computers, all running various applications or monitoring various activities for the business or service provider. Often, to provide the applications or monitoring needed or desired by the business or service provider, very large numbers of computers are required to perform all the various tasks.

15

The rooms in which these computers are located are often very crowded. In addition to each individual computer or system unit, each computer also includes a monitor, a keyboard and mouse. Indeed, it is a common problem that there are often more computers than available space in which to store them.

20

One of the inefficiencies with storing a large number of computers within a finite amount of space is the keyboard redundancy. For every "n" number of

25

30

Docket No. AT9-99-697

computers that are stored, there are typically "n" number of keyboards also stored. However, keyboards are rather large and bulky and take up a rather large amount of space, especially when large numbers of computers are involved, as is typically true in most computer labs. As mentioned above, however, many or most of the computers within the room may be performing functions in which little or no direct human interaction is involved. Often times, the vast majority of computers within the room need a keyboard or other peripheral input device to interact with a computer so infrequently that it does not make sense to store one keyboard for every computer in the room. Therefore, many if not most of the keyboards within the computer lab or room are redundant.

Thus, a system for reducing the number of keyboards required to service a lab full of computers is desirable. It would be even more desirable, if, for some large number of computers, only a few keyboards were needed to service all of the computers within the lab. Thus, a keyboard that can be used with more than one computer is desirable. This arrangement would free up a large amount of space, thereby increasing the capacity of computers that could be stored in the same amount of space.

Docket No. AT9-99-697

### SUMMARY OF THE INVENTION

The present invention minimizes the number of  
5 keyboards required to service a large number of  
computers. In a preferred embodiment, the system  
includes a peripheral input device, such as a keyboard or  
mouse, and a plurality of data processing systems. Each  
of the data processing systems has a wireless receiver  
10 for receiving wireless communications from the peripheral  
input device. The peripheral input device includes a  
computer selector for selecting one of the plurality of  
data processing systems to which the peripheral input  
device will interact. The peripheral input device also  
15 includes a wireless transmitter for providing  
communications with any one of the plurality of data  
processing systems.

Docket No. AT9-99-697

### BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** depicts a block diagram of a data processing system in which the present invention may be implemented;

**Figure 2** depicts a block diagram of an infrared wireless keyboard in which the processes of the present invention may be implemented;

**Figure 3** depicts a pictorial diagram illustrating a room of computers serviced by a single keyboard in accordance with a preferred embodiment of the present invention;

**Figure 4** depicts a flowchart illustrating a method of determining whether a keyboard has been assigned to a data processing system in accordance with a preferred embodiment of the present invention; and

**Figure 5** depicts a flowchart illustrating a method in a keyboard for assigning the keyboard to a particular data processing system in accordance with the present invention.

Docket No. AT9-99-697

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, and in particular with reference to **Figure 1**, a pictorial diagram illustrating a room **100** of computers serviced by a single keyboard is depicted in accordance with a preferred embodiment of the present invention. Room **100** comprises four data processing systems **104**, **106**, **108**, and **110** and a keyboard **102**. Data processing systems **104**, **106**, **108**, and **110** may be implemented, for example, as data processing system **300** described below. Keyboard **102** may be implemented, for example, as infra-red wireless keyboard **200** described below. Keyboard **102** is interoperable with multiple types of data processing systems having different hardware configurations and running different operating systems, thus functioning in a heterogeneous environment.

Referring now to **Figure 2**, a block diagram of an infrared wireless keyboard **200** in which the processes of the present invention may be implemented is illustrated. Infrared wireless keyboard **200** comprises a microprocessor **201**, key matrix **202**, computer select button **203**, infrared driver **204**, power source control circuit **205**, and battery **206**. Computer select button **203** allows a user to select a specific data processing system from a plurality of data processing systems to which keyboard **200** will be assigned by aiming the infrared emitter at the selected data processing system and pushing computer select button **203**.

Keyboard **200** may also include a keyboard select

Docket No. AT9-99-697

on/off switch (not shown). Such an on/off switch would allow a user to activate and deactivate computer select button **203** such that after assigning the keyboard to a computer, computer select button **203** may be deactivated  
5 such that the user can not inadvertently deassign or reassign the keyboard during operation. Once the user decided to deassign or reassign the keyboard to a different computer, the on/off switch is placed in the on position allowing activation of computer select button  
10 **203**.

In operation, microprocessor **201** sends scanning signals to key matrix **202** in order to detect the depression of one of the keys. If no keys are depressed, power source control circuit **205** places microprocessor  
15 **201** into a low-power standby mode. Control circuit **205** also resets microprocessor **201** if power is cut off, ensuring proper microprocessor operation in all cases. If a key has been depressed, control circuit **205** switches microprocessor **201** to a normal operating mode.  
20 Microprocessor **201** assigns a key code to the depressed key according to its position in the key matrix. A data word is then created by microprocessor **201** from the key code. Software within microprocessor **201** then generates a carrier frequency and transmits the data word according  
25 to a known communications format such as RS 232, at the carrier frequency. Infra-red driver **204** emits the data through an infra-red LED.

Referring now to **Figure 3**, a block diagram of a data processing system in which the present invention may be  
30 implemented is illustrated.

Docket No. AT9-99-697

Data processing system **300** is an example of a client computer. Data processing system **300** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures, such as Micro Channel and ISA, may be used. Processor **302** and main memory **304** are connected to PCI local bus **306** through PCI bridge **308**. PCI bridge **308** may also include an integrated memory controller and cache memory for processor **302**. Additional connections to PCI local bus **306** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **310**, SCSI host bus adapter **312**, and expansion bus interface **314** are connected to PCI local bus **306** by direct component connection. In contrast, audio adapter **316**, graphics adapter **318**, and audio/video adapter (A/V) **319** are connected to PCI local bus **306** by add-in boards inserted into expansion slots. Expansion bus interface **314** provides a connection for a keyboard and mouse adapter **320**, modem **322**, and additional memory **324**. Keyboard mouse adapter **320** also provides an interface to a infrared detector and transmitter used to provide wireless communications with a keyboard and/or mouse. In the depicted example, SCSI host bus adapter **312** provides a connection for hard disk drive **326**, tape drive **328**, CD-ROM drive **330**, and digital video disc read only memory drive (DVD-ROM) **332**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **302** and is

Docket No. AT9-99-697

used to coordinate and provide control of various components within data processing system **300** in **Figure 3**. The operating system may be a commercially available operating system, such as OS/2, which is available from  
5 International Business Machines Corporation. "OS/2" is a trademark of International Business Machines Corporation. An object oriented programming system, such as Java, may run in conjunction with the operating system, providing calls to the operating system from Java programs or  
10 applications executing on data processing system **300**. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on a storage device, such as hard disk drive **326**, and may be loaded into main memory **304**  
15 for execution by processor **302**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 3** may vary depending on the implementation. For example, other peripheral devices, such as optical disk drives and the like, may be used in  
20 addition to or in place of the hardware depicted in **Figure 3**. The depicted example is not meant to imply architectural limitations with respect to the present invention. For example, the processes of the present invention may be applied to multiprocessor data  
25 processing systems.

Referring again to **Figure 1**, each of data processing systems **104**, **106**, **108**, and **110** includes an infra-red receiver **120**, **122**, **124**, and **126** respectively. Each of data processing systems **104**, **106**, **108**, and **110** may  
30 comprise different hardware and run a different operating system. For example, data processing systems **104** and **110**

Docket No. AT9-99-697

may be Intel processor based personal computers running Microsoft Windows 98 operating systems, data processing system **106** may be an Apple Macintosh computer running the System 7 operating system, and data processing system **108**  
5 may be an IBM RS/6000, a product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system. Keyboard **102** may select and operate any one of data processing systems **104**, **106**, **108**, and  
10 **110**.

Keyboard **102** includes an infra-red transmitter **130** such connected to an infra-red driver such as infra-red driver **204** for transmitting signals containing key stroke and other information to a data processing system, such  
15 as one of data processing systems **104**, **106**, **108**, and **110**, having an infra-red receiver. Keyboard **102** also includes a computer select button **114**, which a user may use for selecting which of data processing systems **104**, **106**, **108**, and **110** the user wishes to operate.

20 When a user desires to access one of data processing systems **104**, **106**, **108**, and **110**, the user merely aims keyboard **102** at the data processing system to which the user desires access and pushes computer select button **114**. By pushing the computer select button, an infra-red  
25 signal is sent to the desired data processing system instructing that system that keyboard **102** will be communicating with it.

In the example illustrated in **Figure 1**, the user has aimed keyboard **102** at data processing system **108** and has  
30 pushed computer select button **114** to emit a signal **118**

Docket No. AT9-99-697

which is detected by data processing system **108**. Signal **118** alerts data processing system **108** that keyboard **102** is now assigned to data processing system **108**. From this point on, all keystrokes are sent via infra-red (IR) to  
5 the assigned system unit **108**.

When the user wishes to reassign keyboard **102** to a different data processing system, the user merely aims keyboard **102** at a different data processing system and pushes computer select button **114** to send a signal to the  
10 new data processing system that keyboard **102** is now assigned to the new data processing system.

In an alternate embodiment, each of data processing systems **104**, **106**, **108**, and **110** is assigned a code or frequency. Every time a signal is received from keyboard  
15 **102**, each of data processing systems **104**, **106**, **108**, and **110** ignores the signal unless the signal is the code assigned to that particular data processing system indicating that it should respond to all future signals received from keyboard **102**. If such a signal is  
20 received, then the data processing system performs the tasks requested by the signals received from keyboard **102**.

When the user wishes to reassign keyboard **102** to a different data processing system, the user pushes the  
25 computer select button **114** to de-assign keyboard **102** from the selected data processing system. Receipt of a second select signal **118** by a data processing system alerts the data processing system that keyboard **102** is no longer assigned to it. Therefore, it should ignore any further  
30 communication received from keyboard **102** until it has

Docket No. AT9-99-697

been reselected. The user may then assign keyboard **102** to a different data processing system. In this embodiment, computer select button **114** might be a switch that can be toggled between the different codes assigned to the data processing systems or it could comprise a pair of buttons. One of these buttons is used to scroll through a list of computer codes (which may be displayed to the user via a small display such as an LCD on keyboard **102**) by repeatedly pressing it. The other is used to select the appropriate code, once found, to send a signal to activate the appropriate data processing system.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 1** may vary depending on the implementation. For example, more or fewer data processing systems may be utilized than that depicted in **Figure 1**. Furthermore, the present invention is not limited to keyboards, but applies directly to a mouse or any other peripheral device that exchanges data with a computer. The only requirement is that the peripheral device must have the capability of wireless communications with the data processing systems. Also, although described with reference to a single keyboard, there could be multiple keyboards within the computer lab. For example, a lab could contain 50 computers and five keyboards. Furthermore, more than one keyboard could be in operation at one time with, for example, one keyboard communicating with a first computer while a second keyboard is communicating simultaneously with a second computer.

Thus, the present invention allows most of a

Docket No. AT9-99-697

computer lab's keyboards to be discarded, thereby saving space and clutter. The user simply reassigns the keyboard (or one of a few keyboards, if there are more than one) as needed.

5        In another variation of the present invention, other wireless methods of transferring data between the keyboard and the computer could be used. For example, each computer in a computer lab could be equipped with a low power radio frequency (RF) receiver for receiving  
10 communication from a peripheral device having a low power radio frequency (RF) transmitter. Each computer could be assigned to a different radio frequency and each peripheral device could have a button or other selection device for selecting the transmitting frequency. Thus,  
15 if a user wished to access a computer with a keyboard, the user would select the receiving frequency of the computer as the transmitting frequency of the peripheral device.

Referring now to **Figure 4**, a flowchart illustrating  
20 a method of determining whether a keyboard has been assigned to a data processing system is depicted in accordance with a preferred embodiment of the present invention. A data processing system idles until a signal is received from a peripheral device (step **402**). The  
25 data processing system determines whether a signal has been received (step **404**). If no signal has been received, then data processing system continues to idle (step **402**). If a signal has been received, then the data processing system determines if the received signal is a  
30 signal from a peripheral device indicating that that device has assigned itself to this data processing system

Docket No. AT9-99-697

(a computer select signal) (step 406). If the signal is not a computer select signal, then ignore the signal (step 407) and continue to wait for signals (step 402).

If the signal is a computer select signal, then  
5 respond to incoming signals from this device (step 408).  
The data processing device receives the next signal (step 410) and determines whether the signal is a deselect signal (step 412). If the signal is not a deselect signal, then perform the action indicated by the signal  
10 (step 414) and receive the next signal (step 410). if the signal is a deselect signal, then discontinue performing actions in response to signals received from the device (step 416). Note, the deselect signal could be identical to a select signal except for being the  
15 second select signal received from the peripheral device.

Referring now to **Figure 5**, a flowchart illustrating a method in a keyboard for assigning the keyboard to a particular data processing system is depicted in accordance with the present invention. To start, the  
20 keyboard waits for a user to select a computer to which to assign the keyboard (step 502). The keyboard then determines whether a computer has been selected (step 504). If a computer has not been selected, then the keyboard continues to wait for user input (step 502). If  
25 a computer has been selected, then the keyboard must determine which computer has been selected (step 506). The user may select a particular computer by selecting a code or frequency assigned to a particular computer or perhaps by "aiming" the keyboard at the particular  
30 computer or in any number of other manners. Once, the keyboard has determined which computer has been selected,

Docket No. AT9-99-697

the keyboard sends a signal to the selected computer indicating that the keyboard has been assigned to that computer (step **508**).

It is important to note that while the present  
5 invention has been described in the context of a fully  
functioning data processing system, those of ordinary  
skill in the art will appreciate that the processes of  
the present invention are capable of being distributed in  
a form of a computer readable medium of instructions and  
10 a variety of forms and that the present invention applies  
equally regardless of the particular type of signal  
bearing media actually used to carry out the  
distribution. Examples of computer readable media  
include recordable-type media such a floppy disc, a hard  
15 disk drive, a RAM, and CD-ROMs and transmission-type  
media such as digital and analog communications links.

The description of the present invention has been  
presented for purposes of illustration and description,  
but is not intended to be exhaustive or limited to the  
20 invention in the form disclosed. Many modifications and  
variations will be apparent to those of ordinary skill in  
the art. The embodiment was chosen and described in  
order to best explain the principles of the invention the  
practical application and to enable others of ordinary  
25 skill in the art to understand the invention for various  
embodiments with various modifications as are suited to  
the particular use contemplated.